

DETERMINATION OF NON-SIGNIFICANCE

PROPOSAL NAME:	COBU – Lake Restoration for West Lake Sammamish Pkwy. Sinkhole
LOCATION:	2442 and 2436 W Lake Sammamish Pkwy. SE
FILE NUMBERS:	21-107192-LO
PROPONENT:	Abe Santos, City of Bellevue Utilities
DECODIDETION OF DECODO AL	

DESCRIPTION OF PROPOSAL:

City of Bellevue Utilities proposes to remove approximately 150 cubic yards of material deposited in Lake Sammamish, on the shoreline, and in the 100 year floodplain as well as repair an existing stormwater pipe and outfall facility and remove three moorage piles. Following debris removal, the beach and lakebed will be restored and 320 square feet will be planted with native vegetation.

The Environmental Coordinator of the City of Bellevue has determined that this proposal does not have a probable significant adverse impact upon the environment. An Environmental Impact Statement (EIS) is not required under RCW 43.21C.030(2)(C). This decision was made after the Bellevue Environmental Coordinator reviewed the completed environmental checklist and information filed with the Land Use Division of the Development Services Department. This information is available to the public on request.

This DNS is issued after using the optional DNS process in WAC 197-11-355. There is no further comment period on the DNS. There is a 14-day appeal period. Only persons who submitted written comments before the DNS was issued may appeal the decision.

DATE ISSUED: 7/15/2021


APPEAL DATE: 7/29/2021

A written appeal must be filed in the City Clerk's Office by 5 p.m. on the appeal date noted above.

This DNS may be withdrawn at any time if the proposal is modified so as to have significant adverse environmental impacts; if there is significant new information indicating a proposals probable significant adverse environmental impacts (unless a non-exempt license has been issued if the proposal is a private project) or if the DNS was procured by misrepresentation or lack of material disclosure.

Issued By: Elizabeth Stead for Date: July 15, 2021

Elizabeth Stead, Environmental Coordinator Development Services Department



Proposal Name: COBU - Lake Restoration for W Lake Sammamish

Pkwy. Sinkhole

Proposal Address: 2442 and 2436 W Lake Sammamish Pkwy. SE

Proposal Description: City of Bellevue Utilities proposal to remove

approximately 150 cubic yards of material deposited in Lake Sammamish, on the shoreline, and in the 100 year floodplain as well as repair of an existing stormwater pipe and outfall facility and remove three moorage piles. Erosion during repairs to a sinkhole adjacent to W Lake Sammamish Pkwy caused material to travel downslope and into the lake. The proposal is to remove this material, repair a damaged stormwater facility, remove

piles, and restore the beach and lakebed.

File Number: 21-107192-LO

Applicant: Abe Santos, City of Bellevue Utilities

Decisions Included Critical Areas Land Use Permit - (Process II. 20.30P)

Planner: Reilly Pittman, Acting Environmental Planning Manager

State Environmental Policy Act Threshold Determination:

Project Appeal Deadline:

Determination of Non-Significance

By: Elízabeth Stead

for

Elizabeth Stead. Environmental Coordinator

Development Services Department

Director's Decision: Approval with Conditions

By: Elizabeth Stead for

Michael A. Brennan, Director Development Services Department

Development Services Department

Application Date:April 8, 2021Notice of Application Date:May 20, 2021Decision Publication Date:July 15, 2021

For information on how to appeal a proposal, visit Development Services Center at City Hall or call (425) 452-6800. Appeal of the SEPA Threshold Determination or Critical Areas Land Use Permit decision must be made to the City of Bellevue City Clerk's Office by 5 p.m. on the date noted above as the appeal deadline.

July 29, 2021

CONTENTS

I.	Proposal Description	3
II.	Site Description, Zoning, Land Use and Critical Areas	4
III.	Consistency with Land Use Code Requirements	5
IV.	Public Notice and Comment	6
V.	Summary of Technical Reviews	6
VI.	State Environmental Policy Act (SEPA)	6
VII.	Decision Criteria	7
√III.	Conclusion and Decision_	8
IX.	Conditions of Approval	8

Documents Referenced in File

- 1. Project Plans
- 2. Critical Areas Narrative
- 3. Public Comment and Response
- 4. SEPA Checklist

All other documents and materials found in project file

I. Proposal Description

In December of 2019 the City conducted emergency repairs to a sinkhole adjacent to W Lake Sammamish Parkway at 2442 W Lake Sammamish Pkwy SE. The temporary stormwater system was overwhelmed by heavy precipitation which caused erosion and deposition of material down slope onto the shoreline of the adjacent property at 2436 W Lake Sammamish Pkwy. Both sites were restored by the emergency work but approximately 150 cubic yards of material remains within Lake Sammamish and the floodplain along the shoreline. This proposal is to remove this material and restore the beach along the lake to the prior existing condition. Utilities also proposes to reduce the length of a stormwater outfall to be above the Ordinary High Water Mark and construct a new outfall, remove debris and three moorage piles, and plant native vegetation along the shoreline. This proposal includes an associated shoreline exemption application 21-107188-WD. This repair work is within the 100-year floodplain of Lake Sammamish which is a critical area per LUC 20.25H and the proposal requires a Critical Areas Land Use Permit and subject to certain performance standards discussed in this report. See Figure 1 below for project plan and reference document 1.




Figure 1

II. Site Description, Zoning, Land Use and Critical Areas

A. Site Description

The project site is located in the West Lake Sammamish subarea of the City and is within Lake Sammamish, on the shoreline, and in the 100-year floodplain. The project area spans two properties, one which is a private shoreline associated with a single-family residence and the other property being a private communal recreational tract. **See Figure 2 below for project site and vicinity location.**



Figure 2

B. Zoning

The properties at this location are zoned R-3.5 which is a single-family zoning district with three and a half dwelling units per acre expected.

C. Land Use Context

The properties at this location have a Land Use designation of SF-M, Single-Family Medium Density.

D. Critical Areas – Functions and Values

The project area is located in the 100 year floodplain of Lake Sammamish which is a designated critical area. The Land Use Code protects critical areas and their important functions and values described below.

i. Floodplain

a. Floodplain Functions: The value of floodplains can be described in terms of both the hydrologic and ecological functions that they provide. Flooding of occurs when either runoff exceeds the capacity of rivers and streams to convey water within their banks, or when engineered stormwater systems become overwhelmed.

Studies have linked urbanization with increased peak discharge and channel degradation (Dunne and Leopold 1978; Booth and Jackson 1997; Konrad 2000). Floodplains diminish the effects of urbanization by temporarily storing water and mediating flow to downstream reaches. The capacity of a floodplain to buffer upstream fluctuations in discharge may vary according to valley confinement, gradient, local relief, and flow resistance provided by vegetation. Development within the floodplain can dramatically affect the storage capacity of a floodplain, impact the hydrologic regime of a basin, and present a risk to public health and safety and to property and infrastructure.

b. Site Conditions, Impacts and Proposed Mitigation

The 100-year floodplain elevation on Lake Sammamish is all land below elevation 36.1' NAVD 88. The entire project area that is above the Ordinary High Water Mark of Lake Sammamish is within the floodplain. The submitted critical areas study which is reference document 2 finds that the proposal will not result in an increase of the base flood elevation. Communication from the project consultants also references the biological assessment that was submitted under Federal and State permitting that documents the proposal may affect but is not likely to adversely affect Bull Trout, Puget Sound Chinook Salmon, and Puget Sound Steelhead Trout. The project has received concurrence of this finding from NOAA Fisheries and US Fish and Wildlife. The project will remove 150 cubic yards of sediment, debris, old mooring piles as well as plant 320 square feet of native vegetation within 10 feet of the OHWM as mitigation. In addition, an existing storm water pipe will be shortened to ensure the pipe outfall is above the OHWM of the lake to decrease the risk of scour into the lake. The shoreline planting is proposed to be maintained and monitored for five years which complies with land use code 20.25H.220.

III. Consistency with Land Use Code Requirements:

A. Zoning District Dimensional Requirements:

There is no element of this current proposal that is subject to zoning. The project is compatible with the residential recreational uses in vicinity.

B. Critical Areas Requirements LUC 20.25H:

The City of Bellevue Land Use Code Critical Areas Overlay District (LUC 20.25H) establishes performance standards and procedures that apply to development on any site which contains in whole or in part any portion designated as critical area, critical area buffer or structure setback from a critical area or buffer. The project and is subject to the performance standards in LUC 20.25H.180 for work in the area of special flood hazard. The project proposes no development and is removing sediment from the floodplain. As discussed previously, the proposal will not result in a rise of the base flood elevation.

IV. Public Notice and Comment

Application Date: April 8, 2021
Public Notice (500 feet): May 20, 2021
Minimum Comment Period: June 3, 2021

The Notice of Application for this project was published in the City of Bellevue Weekly Permit Bulletin and Seattle Times on May 20, 2021. It was mailed to property owners within 500 feet of the project site. Comments were submitted by email from one resident and a response was provided by the Utilities Department which is found as reference document 3.

V. Summary of Technical Reviews

A. Clearing and Grading

The Clearing and Grading Division of the Development Services Department reviewed the proposal for compliance with Clearing and Grading codes and standards and has approved the application.

B. Utilities

The Utilities Review section of Development Services Department reviewed the proposal for compliance with Utility codes and standards and has approved the application. The reviewer noted that the applicant will need to locate the sewer line in Lake Sammamish and the stormwater line prior to construction which is a submittal requirement on the plans of the future construction permit and not a condition of approval.

VI. State Environmental Policy Act (SEPA)

The environmental review indicates no probability of significant adverse environmental impacts occurring as a result of the proposal. The Environmental Checklist submitted with the application adequately discloses expected environmental impacts associated with the project. The City codes and requirements, including the Clear and Grade Code, Utility Code, Land Use Code, Noise Ordinance, Building Code, and other construction codes are expected to mitigate potential environmental impacts. Therefore, issuance of a Determination of Non-Significance (DNS) is the appropriate threshold determination under the State Environmental Policy Act (SEPA) requirements.

A. Earth, Air, and Water

The proposal will remove 150 cubic yards of sediment that was deposited in the lake and along the shoreline of lake Sammamish. The proposal is to remove this material to restore the prior grade and beach that existed. All work will be done per required clearing and grading best management practices, codes, and standards that will address containment of sediment from the project to the work area.

B. Animals

The proposed work will be done during allowed in-water work windows to avoid impacts to

fish. The applicant will be required to receive State and Federal permit approval. <u>See Conditions of Approval regarding additional agency permitting in Section X of this report.</u>

C. Plants

320 square feet of vegetation is proposed to be planted within 10 feet of the lake. No vegetation is proposed to be impacted by the proposal.

VII. Decision Criteria

A. 20.30P.140 Critical Area Land Use Permit Decision Criteria – Decision Criteria

The Director may approve, or approve with modifications an application for a Critical Area
Land Use Permit if:

1. The proposal obtains all other permits required by the Land Use Code.

<u>Finding:</u> All required construction permits will be obtained. <u>See Conditions of Approval in Section IX of this report.</u>

2. The proposal utilizes to the maximum extent possible the best available construction, design and development techniques which result in the least impact on the critical area and critical area buffer.

<u>Finding:</u> The proposal has only temporary impacts from construction and avoids impacts by working during the allowed work window as well as installing new vegetation.

3. The proposal incorporates the performance standards of Part 20.25H to the maximum extent applicable.

<u>Finding:</u> The proposal incorporates the performance standards discussed in Section III above.

4. The proposal will be served by adequate public facilities including street, fire protection, and utilities.

<u>Finding:</u> The proposal does not impact public services and is improving a stormwater pipe to reduce risk of scour in the lake.

5. The proposal includes a mitigation or restoration plan consistent with the requirements of LUC Section 20.25H.210.

<u>Finding:</u> The proposal includes a mitigation plan consistent with the requirements of LUC 20.25H.210. <u>See Conditions of Approval regarding restoration plans in Section IX of this report.</u>

6. The proposal complies with other applicable requirements of this code.

<u>Finding:</u> As discussed in this report, the proposal complies with all other applicable requirements of the Land Use Code.

VIII. Conclusion and Decision

After conducting the various administrative reviews associated with this proposal, including Land Use Code consistency, City Code and Standard compliance reviews, the Director of the Development Services Department does hereby **approve with conditions** the proposed removal of deposited sediment and restoration within the floodplain of Lake Sammamish.

Approval of this Critical Areas Land Use Permit does not constitute a permit for construction. Separate construction permits are required, and all plans are subject to review for compliance with applicable City of Bellevue codes and standards.

Note- Expiration of Approval: In accordance with LUC 20.30P.150 a Critical Areas Land Use Permit automatically expires and is void if the applicant fails to file for a construction permit or other necessary development permits within one year of the effective date of the approval.

IX. Conditions of Approval

The applicant shall comply with all applicable Bellevue City Codes and Ordinances including but not limited to:

Applicable Ordinances	Contact Person
Clearing and Grading Code- BCC 23.76	Tom McFarlane, 425-452-5207
Utilities Code – BCC Title 24	Mohamed Sambou, 425-452-4853
Land Use Code- BCC Title 20	Reilly Pittman, 425-452-4350

The following conditions are imposed under the Bellevue City Code as referenced:

1. Clearing and Grading Permit Required: Approval of this Critical Areas Land Use Permit does not constitute an approval of any construction permit. A clearing and grading permit must be approved before construction can begin. Plans submitted as part of any permit application shall be consistent with the activity permitted under this approval. A copy of the Hydraulic Project Approval granted by WDFW is required prior to issuance of the clearing and grading permit.

Authority: Land Use Code 20.30P.140, Clearing & Grading Code 23.76.035

Reviewer: Tom McFarlane, Development Services Department

2. Mitigation Planting: The proposed planting of 320 square feet is required as shown on the approved plans.

Authority: Land Use Code 20.25H.210


COBU – Lake Restoration for W Lake Sammamish Pkwy. Sinkhole 21-107192-LO Page 9 of 9

Reviewer: Reilly Pittman, Development Services Department

3. Maintenance and Monitoring: The planting is required to be maintained and monitored as proposed for 5-years per the submitted maintenance and monitoring plan.

Authority: Land Use Code 20.25H.210

Reviewer: Reilly Pittman, Development Services Department



OO' BEVIEW

REMOVE SEDIMENT AS INDICATED ON THE DRAWINGS, NOT TO EXCEED 150 IN-SITU CY.

REMOVE SEDIMENT AND SMOOTH LAKE BED SLOPE TO MATCH PREEXISTING CONDITIONS OR AS DETERMINED IN COORDINATION WITH FIELD ENGINEER.

NO DEBRIS, REFUSE, TRASH, EXCAVATED MATERIAL, DEMOLISHED MATERIAL, OR OTHER FOREIGN MATERIALS OR OBJECTS MAY BE BURIED ON THE SITE OR LEFT IN THE LAKE. REMOVE ALL SUCH MATERIAL FROM THE SITE AND FROM THE LAKE AND DISPOSE OF IN A SAFE AND LEGAL MANNER

PROTECT IN PLACE ALL EXISTING IMPROVEMENTS NOT OTHERWISE NOTED FOR REMOVAL.

INSTALL AND MAINTAIN CONSTRUCTION STABILIZATION AND EROSION CONTROL PER CITY STANDARD NOTES AND DETAILS ON DRAWING C-302

- 1. PROVIDE BOUNDARY SURVEY BY A PROFESSIONAL LAND SURVEYOR LICENSED IN THE STATE OF WASHINGTON TO ESTABLISH PROPERTY CORNERS FOR THE PROJECT SITE.
- 2. LAND SURVEYING MUST BE PERFORMED AND RECORDED TO NAVD 88 VERTICAL DATUM AND NAD 83 HORIZONTAL DATUM
- PROVIDE A PRIVATE LOCATING FIRM TO PERFORM SUBSURFACE UTILITY INVESTIGATION WITHIN THE PROJECT LIMITS. MARK AND PROTECT IN PLACE ANY EXISTING UTILITIES IDENTIFIED WITHIN THE PROJECT LIMITS
- FIELD LOCATE WHERE THE ORDINARY HIGH WATER MARK ELEVATION OF 31.8 FT CROSSES THE EXISTING GROUND, AND STAKE THIS LOCATION AT THE PROPERTY BOUNDARIES AND AT NOT MORE THAN 15 FT INTERVALS BETWEEN. STAKE WITH NEW 2 INCH BY 2 INCH WOODEN STAKES. NOT LESS THAN 2 FEET IN LENGTH, DRIVEN FLUSH TO THE EXISTING GROUND SURFACE AND MARKED WITH 4 FOOT TALL WOODEN LATHE MARKED OHWM. STAKES REMOVED BY THE CONTRACTOR'S ACTIVITIES OR BY GRADING SHALL BE REESTABLISHED BY LICENSED PROFESSIONAL LAND SURVEYOR PRIOR TO FURTHER EXCAVATION OR SEDIMENT REMOVAL.
- PROVIDE TOPGRAPHIC/BATHEMETRIC SURVEY OF THE PROJECT SITE AFTER PLANTING AND SEDIMENT REMOVAL. NOTING THE LOCATION AND ELEVATION OF THE LIMITS OF PLANTING AND GRAVEL REMOVAL. ALSO PROVIDE FINISHED GRADE ELEVATIONS ESTABLISHED BY A GRID PATTERN OF 10 FEET BY 10 FEET WITHIN THE LIMITS OF SEDIMENT REMOVAL.

FENCE NOTES:

- PROVIDE TURBIDITY BARRIER TO MEET SITE TURBIDITY LIMITS.
- PROVIDE TEMPORARY CONSTRUCTION FENCE FOR SITE SAFETY AND TO PREVENT PUBLIC ACCESS TO WORK SUCH AS PILE REMOVAL, SEDIMENT AND DEBRIS REMOVAL, PIPE CUTTING, OPERATION OF EQUIPMENT, ETC

ACCESS NOTES:

- NO VEHICULAR OR EQUIPMENT ACCESS IS ALLOWED TO THE SITE FROM WEST LAKE SAMMAMISH PARKWAY OR ADJACENT PROPERTY, EXCEPT TO DELIVER CONSTRUCTION FENCING, PLANTS AND ESTABLISH SURVEY CONTROL
- 2. ALL MATERIAL DELIVERY, CONSTRUCTION EQUIPMENT DELIVERY, SEDIMENT REMOVAL AND MATERIAL REMOVAL MUST BE PROVIDED VIA BARGE OR BOAT FROM THE LAKE.
- OBTAIN, MAINTAIN, AND ADHERE TO REQUIREMENTS OF LAKE SAMMAMISH STATE PARK SPECIAL USE PERMITS AS APPLICABLE.

PIPE REMOVAL NOTES:

- CUT PIPE PERPENDICULAR TO CENTERLINE OF PIPE.
- REMOVE CUT PIPE AND ANY ASSOCIATED DEBRIS AND DISPOSE OF OFFSITE IN A SAFE AND LEGAL 2 MANNER
- 3. REMOVE BURRS, PROTRUSIONS, OR SHARP EDGES

ABBREVIATIONS

APPROX APPROXIMATE

BOHWM BELOW ORDINARY HIGH WATER MARK

CONSTRUCTION EROSION AND SEDIMENTATION CONTROL CESC CY CLIBIC YARD DIA DIAMETER ELEV **ELEVATION**

INCH LB POUND MIN MINIMUM

OHWM ORDINARY HIGH WATER MARK

SQUARE FEET SO SQUARE TYP TYPICAL

WAC WASHINGTON ADMINISTRATIVE CODE


GRADING NOTES:

- SEDIMENT WAS DEPOSITED ON THE BEACH AND SHORELINE IN 2019 AND 2020. THE GOAL OF THIS WORK IS TO REMOVE SEDIMENT DEPOSITS AND PERFORM FINE GRADING IN ORDER TO RE-ESTABLISH THE ORIGINAL SHORELINE, LAKE BED AND BEACH ELEVATIONS (THE PREEXISTING CONDITION).
- ESTIMATES OF THE ORIGINAL GROUND ELEVATION (PREEXISTING CONDITION), AS WELL AS THE LOCATION AND THICKNESS OF SEDIMENT DEPOSITS INDICATED ON THESE DRAWINGS (EXISTING CONDITION), WERE MADE IN APRIL, 2020. SEDIMENT MAY HAVE MOVED OR CHANGED AFTER THESE MEASUREMENTS WERE MADE; ESTABLISH THE OHWM AND CONFIRM LOCATION AND DEPTH OF SEDIMENT REMOVAL PRIOR TO EXCAVATION

CESC AND TURBIDITY MONITORING NOTES:

- IMPLEMENT BEST MANAGEMENT PRACTICES AND PROVIDE CESC MEASURES AS REQUIRED TO LIMIT SEDIMENTATION AND TURBIDITY TO ACCEPTABLE LIMITS.
- PREPARE, IMPLEMENT, AND MAINTAIN A TURBIDITY MONITORING PLAN IN ACCORDANCE WITH CITY OF BELLEVUE CLEARING AND GRADING DEVELOPMENT STANDARDS CG3-03.3.
- PERFORM TURBIDITY MONITORING AND REPORTING, IN ACCORDANCE WITH THE STATE SURFACE WATER QUALITY STANDARDS (WAC 173.201A-200), TO CONFIRM TURBIDITY DOES NOT EXCEED ACCEPTABLE LIMITS

SECTION / DETAIL DESIGNATIONS





ON DRAWING WHERE ONLY A TITLE IS REQUIRED WITH NO REFERENCE (eg: ELEVATIONS)



SECTION CALLOUT WHERE SECTION IS ON THE SAME SHEET AND CUT



SECTION CALLOUT WHERE SECTION IS ON ANOTHER SHEET AND CUT EXTENDS THROUGHOUT ENTIRE SHEET



NORTH ARROW; CAN BE MODIFIED TO INCLUDE MAGNETIC NORTH ALONG WITH PROJECT NORTH

KEYNOTE NUMBER

 \triangle

REVISION / ADDENDA NUMBER

GRID#

TILITY MILITY

띬 2

24N Σ

4

SEC

NO DATE BY APPR REVISIONS



Approved By

CONSTRUCTION INSPECTOR XXX PROJECT MANAGER

MARCH 2021 DATE

MARCH 2021 DATE

MARCH 2021



2442 WLSP SINKHOLE LAKE RESTORATION

CITY OF BELLEVUE

WASHINGTON


GENERAL

GENERAL NOTES AND SYMBOLS

SHT 2 OF

DWG NO. G-002

REVIEW




REVIEW

- NOTES:
 1. ESTIMATED OHWM IS LOCATED AT 31.8 FT NAVD88 (28.18 FT NGVD) BASED ON 2016 LIDAR. STAKE OHWM PER SURVEY NOTES ON DRAWING G-002.
- 2. THE SITE IS NOT SURVEYED. ALL FEATURES ARE ESTIMATED FROM A COMBINATION OF PARTIAL SURVEYED FEATURES, AS-BUILT RECORDS, AND AERIAL IMAGINARY. CONTRACTOR IS RESPONSIBLE FOR VERIFYING LOCATIONS OF ALL EXISTING AND PROPOSED FEATURES SHOWN ON PLAN.
- REFER TO SPECIFICATION FOR SITE PROTECTION MEASURES AND ACCESS BEFORE ANY GROUND DISTURBANCE BEGINS.
- 4. REFER TO DRAWING C-301 FOR PLANTING NOTES AND DETAILS.

LEGEND OHWM (BASED ON LIDAR) EXISTING PROPERTY LINE EXISTING DRAINAGE OUTFALL SEDIMENT REMOVAL AREA EXISTING STRUCTURE APPROX. PATHWAY

PLANTING LEGEND SCIENTIFIC NAME COMMON NAME SIZE SPACING QUANTITIES BETULA PAPYRIFERA PAPER BIRCH 1.5 CAL. AS SHOWN* ACER CIRCINATUM AS SHOWN* 5 GAL. 2 MAHONIA NERVOSA LOW OREGON-GRAPE 1 GAL. 17 VIBURNUM EDULE HIGHBRUSH CRANBERRY 1 GAL. 3' O.C.

*TREE LOCATIONS SHALL BE FIELD ADJUSTED TO MAINTAIN A MINIMUM OF 5' CLEARANCE FROM EXISTING FENCE AND OTHER UTILITIES.



PLANTING PLAN SCALE: 1"=5'-0"

	NO	DATE	BY	APPR	REVISIONS	
w d						
i.						
2						
٥						
ë						
_						

Jacobs



W A S H W BER GAR	Approved By	
	XXX CONSTRUCTION INSPECTOR	D
JEXP THE PROPERTY OF THE PROPE	XXX PROJECT MANAGER	D



2442 WLSP SINKHOLE LAKE RESTORATION

CITY OF BELLEVUE WASHINGTON

CIVIL **PLANTING PLAN**

DWG NO. SHT 4 OF C-102

REVIEW


UTILITY GRID #


띲

4

NOTES:

- 1. ALL ACCUMULATED DEBRIS SHALL BE COLLECTED FROM CONTAINMENT/ABSORBENT BOOM AND DISPOSED OFFSITE WITHOUT BEING STOCKPILED ON THE SITE.
- 2. SEE DRAWING C-302 FOR ON-SHORE CESC REQUIREMENTS.
- 3. EROSION OR SEDIMENT CONTROL BARRIERS SHALL BE PLACED ALONG THE EDGE OF BARGES HOLDING DEMOLITION DEBRIS AND PILE SECTIONS, TO CONTAIN AND FILTER MATERIAL IN ORDER TO PROTECT WATER QUALITY.
- 4. DEMOLITION DEBRIS, DREDGED AND EXCAVATED MATERIALS SHALL NOT BE STOCKPILED ON THE SITE. IMMEDIATELY REMOVE ALL MATERIALS FROM THE SITE.
- 5. ANY DEPLOYED CONTAINMENT, BOOM OR FILTER STRUCTURE SHALL BE INSPECTED DAILY AND REPAIRED AS NECESSARY TO ENSURE ITS FUNCTION. DEBRIS AND SUBSTANCES COLLECTED IN THE CONTAINMENT, BOOM OR FILTER STRUCTURE SHALL BE REMOVED FROM THE STRUCTURE AT LEAST DAILY, WHENEVER ACCUMULATION PLACES THE STRUCTURE AT RISK, AND BEFORE RELOCATION OR THE REMOVAL OF THE STRUCTURE.
- 6. REFER TO ADDITIONAL GENERAL AND SEDIMENT REMOVAL NOTES ON DRAWING G-002.
- 7. THE SITE IS NOT SURVEYED. ALL FEATURES ARE ESTIMATED FROM A COMBINATION OF PARTIALLY SURVEYED FEATURES, AS-BUILT RECORDS, AND AERIAL IMAGERY. CONTRACTOR IS RESPONSIBLE FOR VERIFYING LOCATIONS OF ALL EXISTING AND PROPOSED FEATURES SHOWN ON PLAN.





SEDIMENT REMOVAL PLAN

NO DATE BY APPR REVISIONS

Jacobs



WILL	Approved
	XXX CONSTRUCTION INSPECTOR
STERED MALE ENGINEER	XXX PROJECT MANAGER





2442 WLSP SINKHOLE LAKE RESTORATION

CITY OF BELLEVUE WASHINGTON

CIVIL

SEDIMENT REMOVAL PLAN

DWG NO.

C-103 SHT 5 OF


UTILITY GRID #

띬

TWP 24N

4

REVIEW




REVIEW

SE UTILITY GRID #

Ä

SEC 17 TWP 24N



PLANTING NOTES:

SITE IS NOT SURVEYED. CONTRACTOR SHALL VERIFY ALL EXISTING FEATURES AND UTILITIES LOCATIONS. PROTECT IN PLACE BEFORE ANY GROUND DISTURBANCE.

 IDENTIFY WORK LIMIT FROM SHEET C-102. PROTECT EXISTING SWORD FERNS AND TREE STUMPS TO REMAIN. GRUB OUT OTHER SHRUBS, GRASSES, AND GARDEN WEEDS FROM THEIR ROOTS AND DISPOSE OFF-SITE.

ROTOTILL 4" OF TOPSOIL TYPE A OR APPROVED ORGANIC AMENDMENT INTO THE EXISTING SUBGRADE TO A MINIMUM TRANSITION DEPTH OF SIX (6) INCHES OVER THE ENTIRE PLANTING AREA. AMEND AREA WITH EXISTING SWORD FERNS BY PLACING 2" TOPSOIL LOOSELY OVER TOP OF THE VEGETATION

- 4. LAYOUT PLANTS PER SHEET C-102 AND FIELD ADJUST TO EXISTING SITE FEATURES. PLANT LAYOUT MUST BE APPROVED BY CITY OR CITY REPRESENTATIVE BEFORE
- 5. INSTALL PLANT MATERIAL ACCORDING TO SPECIFICATION SECTION 8-02 AND PLANTING DETAILS SHOWN ON SHEET C-301.
- APPLY WOOD MULCH OVER THE ENTIRE SHORELINE RESTORATION AREA, INCLUDING EXISTING SWORD FERNS AND AROUND THE TREE STUMPS
- WATER THE NEW PLANTINGS THOROUGHLY ON THE SAME DAY OF INSTALLATION. AT THE DIRECTION OF THE CITY OR ITS REPRESENTATIVE, TREE GATOR BAGS OR TEMPORARY IRRIGATION SYSTEM MIGHT BE REQUIRED DURING THE PLANT ESTABLISHMENT PERIOD
- 8. REMOVE ALL IMPORTED DEBRIS AND RESTORE WORK AREA ACCORDINGLY TO THE

TYPICAL TREE PLANTING DETAIL

3" DEPTH WOOD MULCH. -KEEP MULCH AWAY SHRUB OR GROUNCOVER PER PLAN FROM FOLIAGE AND ROOT CROWN GRADE AT WHICH PLANT MOUND SOIL TO GREW IN NURSERY. DO NOT FORM 4" HIGH BURY ROOT CROWN. IRRIGATION BASIN, TYP. CONTAINERIZED: REMOVE CONTAINER, ROUGH UP ROOT BALL AND SPREAD ROOTS TO PROMOTE ELONGATION INTO NATIVE SOIL. SCARIFY SIDES OF PLANTING HOLE, TYP. 2X DIA. OF ROOT BALL, TYP. NATIVE SOIL BACKFILL. INCORPORATE UP TO 25% OF TYPE A TOPSOIL OR COMPOST AMENDMENT IN THE PLANTING PIT UNDISTURBED OR AMENDED NATIVE SOIL

TYPICAL SHRUB OR GROUNDCOVER PLANTING DETAIL

NO DATE BY APPR REVISIONS

Jacobs



CONSTRUCTION INSPECTOR XXX PROJECT MANAGER

2442 WLSP SINKHOLE LAKE RESTORATION

CITY OF BELLEVUE WASHINGTON

DWG NO. C-301 SHT 7 OF GRID# TILITY MILITY 띬

2 TWP 24N 4

REVIEW

PROVIDE 2 SPARE LINKS MIN. TO -

OF TRUNK

NOTES:
1. CONTAINERIZED TREES: REMOVE

2. STAKING IS REQUIRED FOR TREES

5'-0" OR GREATER IN HEIGHT

3. ALTERNATIVE STAKING METHODS

TREES WITH 3" CALIPER OR

5. STAKES SHALL BE REMOVED NO

LATER THAN 1 YEAR AFTER TREE

PLANTING UNLESS OTHERWISE

TREES SHALL BE INSPECTED AND APPROVED BY BELLEVUE PARKS

OR REPRESENTATIVE PRIOR TO

INSTALLATION.

MAY BE ACCEPTED WITH

UNLESS OTHERWISE SPECIFIED.

APPROVAL OF BELLEVUE PARKS OR REPRESENTATIVE.
4. 3 STAKES MAY BE REQUIRED FOR

CONTAINER, ROUGH UP ROOT BALL

AND SPREAD ROOTS TO PROMOTE ELONGATION INTO NATIVE SOIL.

POSITION TIE WITH 1/3" MIN.

CLEARANCE ON ALL SIDES

ALLOW FOR TENSION ADJUSTMENT

Approved By

MARCH 2021 DATE MARCH 2021 DATE

CIVIL

NO DATE BY APPR

REVISIONS

posts. Use staples, wire rings or 2"x2" by 14 Ga. wire or equivalent, if standard equivalent to attach fabric to posts strength fabric used Filter fabric 6' max Minimum 4"x4" trench Backfill trench with native soil or 3/4"-1.5" washed gravel Post spacing may be increased to 8' if wire backing is used Steel fence posts or equivalent

SILT FENCE STANDARD DETAILS

STANDARD NOTES FOR EROSION CONTROL PLANS

Joints in filter fabric shall be spliced at

ALL CLEARING & GRADING CONSTRUCTION MUST BE IN ACCORDANCE WITH CITY OF BELLEVUE (COB) CLEARING & GRADING CODE, CLEARING & GRADING DEVELOPMENT STANDARDS, LAND USE CODE, UNIFORM BUILDING CODE, PERMIT CONDITIONS, AND ALL OTHER APPLICABLE CODES, ORDINANCES, AND STANDARDS, THE DESIGN ELEMENTS WITHIN THESE PLANS HAVE BEEN REVIEWED ACCORDING TO THESE REQUIREMENTS. ANY VARIANCE FROM ADOPTED EROSION CONTROL STANDARDS IS NOT ALLOWED UNLESS SPECIFICALLY APPROVED BY THE CITY OF BELLEVUE DEVELOPMENT SERVICES (DSD) PRIOR TO CONSTRUCTION. IT SHALL BE THE SOLE RESPONSIBILITY OF THE APPLICANT AND THE PROFESSIONAL CIVIL ENGINEER TO

ERROR, OMISSION, OR VARIATION FROM THE ABOVE REQUIREMENTS FOUND IN THESE PLANS. ALL CORRECTIONS SHALL BE AT NO ADDITIONAL COST OR LIABILITY TO THE COB.

- APPROVAL OF THIS EROSION/SEDIMENTATION CONTROL (ESC) PLAN DOES NOT CONSTITUTE AN APPROVAL OF PERMANENT ROAD OR DRAINAGE DESIGN (E.G. SIZE AND LOCATION OF ROADS, PIPES, RESTRICTORS, CHANNELS, RETENTION FACILITIES,
- A COPY OF THE APPROVED PLANS AND DRAWINGS MUST BE ON-SITE DURING CONSTRUCTION. THE APPLICANT IS RESPONSIBLE FOR OBTAINING ANY OTHER REQUIRED OR RELATED PERMITS PRIOR TO BEGINNING CONSTRUCTION.
- THE IMPLEMENTATION OF THESE ESC PLANS AND THE CONSTRUCTION, MAINTENANCE, REPLACEMENT, AND UPGRADING OF THESE ESC FACILITIES IS THE RESPONSIBILITY OF THE APPLICANT/CONTRACTOR UNTIL ALL CONSTRUCTION IS COMPLETED AND APPROVED AND VEGETATION/LANDSCAPING IS ESTABLISHED.
- THE ESC FACILITIES SHOWN ON THIS PLAN MUST BE CONSTRUCTED IN CONJUNCTION WITH ALL CLEARING AND GRADING ACTIVITIES, AND IN SUCH A MANNER AS TO ENSURE THAT SEDIMENT AND SEDIMENT LADEN WATER DO NOT ENTER THE DRAINAGE SYSTEM, ROADWAYS, OR VIOLATE APPLICABLE WATER STANDARDS
- THE ESC FACILITIES SHOWN ON THIS PLAN ARE THE MINIMUM REQUIREMENTS FOR ANTICIPATED SITE CONDITIONS. DURING THE CONSTRUCTION PERIOD, THESE ESC FACILITIES SHALL BE UPGRADED AS NEEDED FOR UNEXPECTED STORM EVENTS AND TO ENSURE THAT SEDIMENT AND SEDIMENT-LADEN WATER DO NOT LEAVE THE SITE.
- ALL LOCATIONS OF EXISTING UTILITIES HAVE BEEN ESTABLISHED BY FIELD SURVEY OR OBTAINED FROM AVAILABLE RECORDS AND SHOULD, THEREFORE, BE CONSIDERED ONLY APPROXIMATE AND NOT NECESSARILY COMPLETE. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO INDEPENDENTLY VERIFY THE ACCURACY OF ALL UTILITY LOCATIONS AND TO DISCOVER AND AVOID ANY OTHER UTILITIES NOT SHOWN WHICH MAY BE AFFECTED BY THE IMPLEMENTATION OF THIS PLAN
- THE BOUNDARIES OF THE CLEARING LIMITS SHOWN ON THIS PLAN SHALL BE CLEARLY FLAGGED IN THE FIELD PRIOR TO CONSTRUCTION. DURING THE CONSTRUCTION PERIOD, NO DISTURBANCE BEYOND THE FLAGGED CLEARING LIMITS SHALL BE PERMITTED. THE FLAGGING SHALL BE MAINTAINED BY THE APPLICANT/CONTRACTOR FOR THE DURATION OF CONSTRUCTION
- CLEARING SHALL BE LIMITED TO THE AREAS WITHIN THE APPROVED DISTURBANCE LIMITS. EXPOSED SOILS MUST BE COVERED AT THE END OF EACH WORKING DAY WHEN WORKING FROM OCTOBER 1ST THROUGH APRIL 30TH. FROM MAY 1ST THROUGH SEPTEMBER 30TH, EXPOSED SOILS MUST BE COVERED AT THE END OF EACH CONSTRUCTION WEEK AND AT THE THREAT OF
- 10. AT NO TIME SHALL MORE THAN ONE FOOT OF SEDIMENT BE ALLOWED TO ACCUMULATE WITHIN A TRAPPED CATCH. ALL CATCH BASINS AND CONVEYANCE LINES SHALL BE CLEANED PRIOR TO PAVING. THE CLEANING OPERATION SHALL NOT FLUSH SEDIMENT LADEN WATER INTO THE DOWNSTREAM SYSTEM.
- 11. STABILIZED CONSTRUCTION ENTRANCES SHALL BE INSTALLED AT THE BEGINNING OF CONSTRUCTION AND MAINTAINED FOR THE DURATION OF THE PROJECT.
- 12. THE CONTRACTOR MUST MAINTAIN A SWEEPER ON SITE DURING EARTHWORK AND IMMEDIATELY REMOVE SOIL THAT HAS BEEN TRACKED ONTO PAVED AREAS AS RESULT OF CONSTRUCTION.
- 13. THE ESC FACILITIES SHALL BE INSPECTED DAILY BY THE APPLICANT/CONTRACTOR AND MAINTAINED AS NECESSARY TO ENSURE THEIR CONTINUED FUNCTIONING.
- 14. ANY EXCAVATED MATERIAL REMOVED FROM THE CONSTRUCTION SITE AND DEPOSITED ON PROPERTY WITHIN THE CITY LIMITS MUST BE DONE IN COMPLIANCE WITH A VALID CLEARING & GRADING PERMIT. LOCATIONS FOR THE MOBILIZATION AREA AND STOCKPILED MATERIAL MUST BE APPROVED BY THE CLEARING AND GRADING INSPECTOR AT LEAST 24 HOURS IN ADVANCE OF
- 15. THE ESC FACILITIES ON INACTIVE SITES SHALL BE INSPECTED AND MAINTAINED A MINIMUM OF ONCE A MONTH OR WITHIN THE 48 HOURS FOLLOWING A MAJOR STORM EVENT.
- 16. FINAL SITE GRADING MUST DIRECT DRAINAGE AWAY FROM ALL BUILDING STRUCTURES AT A MINIMUM 5% SLOPE, PER THE INTERNATIONAL RESIDENTIAL CODE (IRC) R401.3.
- 17. INSTALL AND MAINTAIN CONSTRUCTION STABILIZATION AND EROSION CONTROL PER CITY STANDARD NOTES AND DETAILS

ANCHOR

- ADD OIL BOOM

SHORELINE

Approved By CONSTRUCTION INSPECTOR PROJECT MANAGER

TURBIDITY BARRIER GENERAL NOTES:

STANDARD SPECIFICATIONS AND THE APPLICABLE

TURBIDITY BARRIER MAY BE REMOVED AT THE

CONTROL MEASURES HAVE BEEN ESTABLISHED.

1) DRIVEN STEEL POSTS, PIPES, OR CHANNELS. LENGTH SHALL BE SUFFICIENT TO SECURELY SUPPORT BARRIER

(2) SANDBAGS TO BE USED AS ADDITIONAL BALLAST WHEN

CONDITIONS, SPACE AS APPROPRIATE FOR SITE

(3) WHEN BARRIER HEIGHT, H, EXCEEDS 8 FT., POST

(4) IN WATERWAYS SUBJECT TO FLUCTUATING WATER

THE WATER TO EQUALIZE ON EACH SIDE OF THE

SPACING MAY NEED TO BE DECREASED.

(5) ESTIMATED HIGH WATER ELEVATION DURING

(7) ALLOW SUFFICIENT SLACK VERTICALLY AND

INSTALLATION OF POSTS.

CONDITIONS

ORDERED BY THE ENGINEER TO MEET ADVERSE FIELD

ELEVATIONS, PROVISIONS SHOULD BE MADE TO ALLOW

BARRIER. THIS MAY BE ACCOMPLISHED BY LEAVING A

PORTION OF THE BARRIER OPEN ON THE UPSTREAM

CONSTRUCTION PERIOD. MINIMUM BARRIER HEIGHT

WRITTEN APPROVAL OF THE ENGINEER, AND IS MEANT

HORIZONTALLY SO THAT SEDIMENT BUILD UP WILL NOT

FOR LOCATIONS WHERE BEDROCK PREVENTS THE

SHALL BE 2' GREATER THAN THE ESTIMATED HIGH

WATER ELEVATION DURING CONSTRUCTION.

(6) FLOAT ALTERNATIVE WILL ONLY BE ALLOWED WITH

SEPARATE OR LOWER THE TURBIDITY BARRIER.

WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE

ENGINEERS DISCRETION, WHEN PERMANENT EROSION

DETAILS OF CONSTRUCTION, MATERIALS AND





2442 WLSP SINKHOLE LAKE RESTORATION

CITY OF BELLEVUE

CESC DETAILS

CIVIL

DWG NO. C-302 SHT 8 OF 뗥 \$ ₹ 4

얦

띯

REVIEW

Jacobs

WASHINGTON